




EBARA

SPECIFICATIONS

50Hz

Rev. G

EVM(.) 32-64

PUMP					
Type		EVMG	EVM	EVML	
Liquid Handled	Type of liquid	Clean water, water contains glycol and moderately aggressive fluids			
	Temperature [°C]	-15 to +120			
	Max solid content	50 ppm (Particle size 0,1-0,25mm or less)			
	Max chlorine ion density	500 ppm			
Maximum working pressure		[MPa]	1.6 / 3.0		
		[bar]	16 / 30		
Construction	Impeller	Closed centrifugal type			
	Shaft seal type	Mechanical seal			
	Bearing	Sealed ball bearing with permanent grease			
Pipe connection	Suction /Discharge	See the dimension table			
Material	Impeller	EN 1.4301(AISI 304)		EN 1.4401 (AISI 316)	
	Intermediate casing	EN 1.4301(AISI 304)		EN 1.4401 (AISI 316)	
	Bottom casing	Cast iron	ASTM CF8	ASTM CF8M	
	Casing cover	Cast iron	Cast iron + EN 1.4301 (AISI 304)	Cast iron + EN 1.4401 (AISI 316)	
	Outer casing	EN 1.4301(AISI 304)		EN 1.4401 (AISI 316)	
	Shaft	EN 1.4401 (AISI 316)			
	Liner ring	EVM32	PTFE / EN 1.4301 (AISI 304)		PTFE / EN 1.4401 (AISI 316)
		EVM45,64	PTFE / EN 1.4401 (AISI 316)		
	Motor bracket	Cast iron			
	Mechanical Seal	Silicon Carbide/Carbon/FPM			
	O-Ring	EPDM	EPDM	FPM	
Applicable standard of test		ISO 9906 annex A			

MOTOR			
Type		Electric -TEFC	
		Single phase	Three phase
Efficiency		/	IE2 from 2.2 kW up to 37 kW
No. of Poles		2	
Rotation speed [min-1]		≈ 2900	
Insulation class		Class F (class B for temperature rise)	
Protection form		IP 55	
Power rating	[kW]	2.2	2.2*37
	[HP]	3	3.0*50
Frequency [Hz]		50	
Voltage [V]		230 ± 10 %	230/400 ± 10% (up to 4 kW) 400/690 ± 10% (above 5.5 kW)
Over load protection		User to provide	
Casing material		Aluminium	
Flange mount (IEC motor)		IM B14 (up to 4 kW)	
		IM B5 (above 5.5 kW)	

SELECTION CHART


50Hz

Rev. G

EVM(.) 32-64


Pump Type EVM(.)	Motor			Maximum working pressure [Mpa]	Q=Capacity																	
	kW	HP	Size		l/min		200		350		500		700		900		1000		1200		1400	
					0	0	12	12	21	30	30	42	54	60	60	72	84					
					m³/h		H=Total		manometric		head		in		meters							
32 1-0F5/2.2	2.2	3	90L	1.6	24	21.7	19.6	16.4	13.2	9.7	-	-	-	-	-	-	-	-	-	-		
32 2-2F5/3.0	3	4	100		39.8	36.9	31.6	23.5	17.4	-	-	-	-	-	-	-	-	-	-	-		
32 2-0F5/4.0	4	5.5	112		48	43.5	39.2	32.8	26.5	19.4	-	-	-	-	-	-	-	-	-	-		
32 3-3F5/5.5	5.5	7.5	132S		59.5	55.5	47.5	35.2	26.1	-	-	-	-	-	-	-	-	-	-	-		
32 3-1F5/5.5	5.5	7.5	132S		68	62	55	44.5	35.2	24.5	-	-	-	-	-	-	-	-	-	-		
32 4-3F5/7.5	7.5	10	132S		84	77	67.0	51.5	39.4	-	-	-	-	-	-	-	-	-	-	-		
32 4-1F5/7.5	7.5	10	132S		92	83.5	74.5	61	48.5	34.2	-	-	-	-	-	-	-	-	-	-		
32 5-3F5/11	11	15	160M		106	100	89	70	54	37.3	-	-	-	-	-	-	-	-	-	-		
32 5-0F5/11	11	15	160M		118	110	100	84	67	49	-	-	-	-	-	-	-	-	-	-		
32 6-3F5/11	11	15	160M		130	122	109	87	67.5	47	-	-	-	-	-	-	-	-	-	-		
32 6-2F5/11	11	15	160M		133	125	113	91.5	71.5	51	-	-	-	-	-	-	-	-	-	-		
32 7-3F5/15	15	20	160M		153	144	129	104	81	57	-	-	-	-	-	-	-	-	-	-		
32 7-0F5/15	15	20	160M		165	154	141	118	94	69	-	-	-	-	-	-	-	-	-	-		
32 8-3F5/15	15	20	160M		177	166	150	121	94.0	67	-	-	-	-	-	-	-	-	-	-		
32 8-1F5/15	15	20	160M		184	172	157	130	103	75	-	-	-	-	-	-	-	-	-	-		
32 9-3F5/18.5	18.5	25	160L	200	188	170	137	108	76.5	-	-	-	-	-	-	-	-	-	-			
32 9-0F5/18.5	18.5	25	160L	2.5	212	197	181	152	121	88.5	-	-	-	-	-	-	-	-	-			
32 10-3F5/18.5	18.5	25	160L		224	210	190	154	121	86.5	-	-	-	-	-	-	-	-	-	-		
32 10-2F5/18.5	18.5	25	160L		228	213	193	159	125	90.5	-	-	-	-	-	-	-	-	-	-		
32 11-3F5/22	22	30	180		247	232	210	171	134	96.5	-	-	-	-	-	-	-	-	-	-		
32 11-0F5/22	22	30	180		259	241	221	185	147	108	-	-	-	-	-	-	-	-	-	-		
32 12-3F5/22	22	30	180		271	254	230	188	148	106	-	-	-	-	-	-	-	-	-	-		
32 13-3F5/30	30	40	200		294	276	250	205	161	116	-	-	-	-	-	-	-	-	-	-		
32 13-0F5/30	30	40	200		306	285	261	219	174	128	-	-	-	-	-	-	-	-	-	-		
32 14-3F5/30	30	40	200	318	298	270	222	175	126	-	-	-	-	-	-	-	-	-	-			
32 14-0F5/30	30	40	200	330	307	281	236	188	138	-	-	-	-	-	-	-	-	-	-			
45 1-1F5/3.0	3	4	100	1.6	21.0	-	18.9	17.6	16.3	14.3	8.3	-	-	-	-	-	-	-	-			
45 1-0F5/4.0	4	5.5	112		27.0	-	25.6	24.6	23.5	21.8	16.7	13.3	-	-	-	-	-	-	-	-		
45 2-2F5/5.5	5.5	7.5	132S		42.0	-	38.1	35.8	33.4	29.8	18.6	-	-	-	-	-	-	-	-	-		
45 2-0F5/7.5	7.5	10	132S		54.0	-	51.5	50	48	45	35.4	29.1	-	-	-	-	-	-	-	-		
45 3-2F5/11	11	15	160M		69.0	-	64	61	58	53	37.3	-	-	-	-	-	-	-	-	-		
45 3-0F5/11	11	15	160M		81.0	-	77.5	75	72.5	68	54	45	-	-	-	-	-	-	-	-		
45 4-2F5/15	15	20	160M		96.0	-	90	86	82	76	56	43	-	-	-	-	-	-	-	-		
45 4-0F5/15	15	20	160M		108.0	-	103	100	96.5	91	73	60.5	-	-	-	-	-	-	-	-		
45 5-2F5/18.5	18.5	25	160L		123.0	-	116	111	107	99.0	74.5	58.5	-	-	-	-	-	-	-	-		
45 5-0F5/18.5	18.5	25	160L		135.0	-	129	125	121	114	91.5	76.5	-	-	-	-	-	-	-	-		
45 6-2F5/22	22	30	180		150.0	-	142	137	131	122	93.5	74.5	-	-	-	-	-	-	-	-		
45 6-0F5/22	22	30	180		2.5	162.0	-	155	151	146	137	110	92.5	-	-	-	-	-	-	-		
45 7-2F5/30	30	40	200			177.0	-	168	162	155	145	112	90.5	-	-	-	-	-	-	-	-	
45 7-0F5/30	30	40	200			189.0	-	181	176	170	160	129	108	-	-	-	-	-	-	-	-	
45 8-2F5/30	30	40	200			204.0	-	194	187	180	168	131	106	-	-	-	-	-	-	-	-	
45 8-0F5/30	30	40	200	216.0		-	207	201	194	183	148	124	-	-	-	-	-	-	-	-		
45 9-2F5/30	30	40	200	231.0		-	219	212	204	191	150	122	-	-	-	-	-	-	-	-		
45 9-0F5/37	37	50	200	243.0		-	233	226	219	206	166	140	-	-	-	-	-	-	-	-		
45 10-2F5/37	37	50	200	3.0		258.0	-	245	237	229	214	168	138	-	-	-	-	-	-	-		
45 10-0F5/37	37	50	200		270.0	-	259	251	243	229	185	156	-	-	-	-	-	-	-	-		
64 1-1F5/4.0	4	5.5	100		23.7	-	-	21	20.4	19.7	17.5	15.9	11.4	-	-	-	-	-	-	-		
64 1-0F5/5.5	5.5	7.5	132S		29.3	-	-	26.6	26.1	25.4	23.7	22.3	18.5	13.5	-	-	-	-	-	-		
64 2-2F5/7.5	7.5	10	132S		47.5	-	-	42.5	41.5	40.5	36.5	33.5	25.3	-	-	-	-	-	-	-		
64 2-1F5/11	11	15	160M		53.0	-	-	48	47	46	42.5	40	32.4	23	-	-	-	-	-	-		
64 2-0F5/11	11	15	160M		58.5	-	-	53.5	53	52	49	46.5	39.5	30.6	-	-	-	-	-	-		
64 3-3F5/15	15	20	160M		71.0	-	-	64	62.5	61	55.5	51	39.3	-	-	-	-	-	-	-		
64 3-2F5/15	15	20	160M	1.6	76.5	-	-	69.5	68	66.5	61.5	57.5	46.5	32.5	-	-	-	-	-	-		
64 3-1F5/15	15	20	160M		82.5	-	-	75	74	72.5	68	64	53.5	40	-	-	-	-	-	-		
64 3-0F5/18.5	18.5	25	160L		88.0	-	-	80.5	79.5	78	74	70.5	60.5	47.5	-	-	-	-	-	-		
64 4-3F5/18.5	18.5	25	160L		100.0	-	-	91	89	87	80.5	75.5	60.5	42	-	-	-	-	-	-		
64 4-2F5/18.5	18.5	25	160L		106.0	-	-	96.5	95	93	87	81.5	67.5	49.5	-	-	-	-	-	-		
64 4-1F5/22	22	30	180		112.0	-	-	102	101	98.5	93	88	74.5	57	-	-	-	-	-	-		
64 4-0F5/22	22	30	180		117.0	-	-	108	106	104	99.0	94.5	81.5	64.5	-	-	-	-	-	-		
64 5-3F5/30	30	40	200		130.0	-	-	118	116	114	106	99.5	81.5	59.0	-	-	-	-	-	-		
64 5-2F5/30	30	40	200		135.0	-	-	124	122	119	112	106	88.5	66.5	-	-	-	-	-	-		
64 5-1F5/30	30	40	200		141.0	-	-	129	127	125	118	112	95.5	74.0	-	-	-	-	-	-		
64 5-0F5/30	30	40	200		147.0	-	-	135	133	131	124	119	103	81.5	-	-	-	-	-	-		
64 6-3F5/30	30	40	200		2.5	159.0	-	-	145	143	140	131	124	103	76.0	-	-	-	-	-		
64 6-2F5/30	30	40	200			165.0	-	-	151	148	146	137	130	110	83.5	-	-	-	-	-	-	
64 6-1F5/37	37	50	200	170.0		-	-	156	154	151	143	136	117	91.0	-	-	-	-	-	-		
64 6-0F5/37	37	50	200	176.0		-	-	162	160	157	149	143	124	99.0	-	-	-	-	-	-		
64 7-3F5/37	37	50	200	188.0		-	-	172	169	166	156	148	124	93.0	-	-	-	-	-	-		
64 7-2F5/37	37	50	200	194.0		-	-	178	175	172	162	154	131	101	-	-	-	-	-	-		
64 7-1F5/37	37	50	200	200.0		-	-	183	181	178	168	161	138	108	-	-	-	-	-	-		
64 7-0F5/37	37	50	200	206.0		-	-	189	186	183	173	165	143	111	-	-	-	-	-	-		

EVM64 1-1 F5 4.0 (4.0kW) MEI > 0.70 no.1 impeller diameter= 131 mm
EVM64 1-0 F5 5.5 (5.5kW) MEI > 0.70 no.1 impeller diameter= 143 mm



Rotation speed $\approx 2900 \text{ min}^{-1}$
 Test standard: ISO 9906-Annex A

EVM64 2-2 F5 7.5 (7.5kW) MEI > 0.70 no.2 impellers diameter = 131 mm
 EVM64 2-1 F5 11 (11kW) MEI > 0.70 no.1 impeller diameter = 143 mm / no.1 impeller diameter = 131mm
 EVM64 2-0 F5 11 (11kW) MEI > 0.70 no.2 impellers diameter = 143 mm




Rotation speed $\approx 2930 \text{ min}^{-1}$
 Test standard: ISO 9906-Annex A

PERFORMANCE CURVE

50Hz

Rev. G

EVM64 3-3 F5 15 (15kW) MEI > 0.70 no.3 impellers diameter = 131 mm
 EVM64 3-2 F5 15 (15kW) MEI > 0.70 no.1 impeller diameter = 143 mm / no.2 impellers diameter = 131mm
 EVM64 3-1 F5 15 (15kW) MEI > 0.70 no.2 impellers diameter = 143 mm / no.1 impeller diameter = 131mm
 EVM64 3-0 F5 18.5 (18.5kW) MEI > 0.70 no.3 impellers diameter = 143 mm




Rotation speed $\approx 2940 \text{ min}^{-1}$
 Test standard: ISO 9906-Annex A

PERFORMANCE CURVE

50Hz

Rev. G

EVM64 4-3 F5 18.5 (18.5kW) MEI > 0.70 no.1 impeller diameter = 143 mm/no.3 impellers diameter = 131mm
 EVM64 4-2 F5 18.5 (18.5kW) MEI > 0.70 no.2 impellers diameter = 143 mm/no.2 impellers diameter=131mm
 EVM64 4-1 F5 22 (22kW) MEI > 0.70 no.3 impellers diameter = 143 mm / no.1 impeller diameter = 131mm
 EVM64 4-0 F5 22 (22.5kW) MEI > 0.70 no.4 impellers diameter = 143 mm




Rotation speed $\approx 2940 \text{ min}^{-1}$
 Test standard: ISO 9906-Annex A

PERFORMANCE CURVE

50Hz

Rev. G

EVM64 5-3 F5 30 (30kW) MEI > 0.70 no.2 impellers diameter = 143 mm / no.3 impellers diameter = 131mm
 EVM64 5-2 F5 30 (30kW) MEI > 0.70 no.3 impellers diameter = 143 mm / no.2 impellers diameter = 131mm
 EVM64 5-1 F5 30 (30kW) MEI > 0.70 no.4 impellers diameter = 143 mm / no.1 impeller diameter = 131mm
 EVM64 5-0 F5 30 (30kW) MEI > 0.70 no.5 impellers diameter = 143 mm




Rotation speed $\approx 2960 \text{ min}^{-1}$
 Test standard: ISO 9906-Annex A

PERFORMANCE CURVE

50Hz

Rev. G

EVM64 6-3 F5 30 (30kW) MEI > 0.70 no.3 impellers diameter = 143 mm / no.3 impellers diameter = 131mm
 EVM64 6-2 F5 30 (30kW) MEI > 0.70 no.4 impellers diameter = 143 mm / no.2 impellers diameter = 131mm
 EVM64 6-1 F5 37 (37kW) MEI > 0.70 no.5 impellers diameter = 143 mm / no.1 impeller diameter = 131mm
 EVM64 6-0 F5 37 (37kW) MEI > 0.70 no.6 impellers diameter = 143 mm



Rotation speed $\approx 2960 \text{ min}^{-1}$
 Test standard: ISO 9906-Annex A

PERFORMANCE CURVE


50Hz

Rev. G

EVM64 7-3 F5 37 (37kW) MEI > 0.70 no.4 impellers diameter = 143 mm / no.3 impellers diameter = 131mm


EVM64 7-2 F5 37 (37kW) MEI > 0.70 no.5 impellers diameter = 143 mm / no.2 impellers diameter = 131mm

EVM64 7-1 F5 37 (37kW) MEI > 0.70 no.6 impellers diameter = 143 mm / no.1 impeller diameter = 131mm



Rotation speed $\approx 2960 \text{ min}^{-1}$
Test standard: ISO 9906-Annex A

EVM(.) 32-64



See dimensions pages 404,405,406

DIMENSIONS TABLE EVM(.) 64

Pump Type EVM	Pmax. [MPa] 2)	Motor Size	Dimensions [mm]																			Weight [kgf]		
			H	H2	H3 1) 3~	E	B 1) 3~	C 1) 3~	BM	BL	BY1	BW	SA	SG	D1	D2	H8	SN	D3	BF	BH	A	Pump	Pump + motor
64 1-1F5/4.0	1.6	112	140	525	306	365	196	155	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	160	70.4	93.2
64 1-0F5/5.5	1.6	132	140	546	328	365	220	161	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	300	77.0	115.6
64 2-2F5/7.5	1.6	132	140	618	328	365	220	161	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	300	81.4	121.8
64 2-1F5/11	1.6	160M	140	749	403	365	248	195	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	350	93.5	156.0
64 2-0F5/11	1.6	160M	140	749	403	365	248	195	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	350	93.5	156.0
64 3-3F5/15	1.6	160M	140	821	498	365	317	238	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	350	99.0	186.1
64 3-2F5/15	1.6	160M	140	821	498	365	317	238	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	350	99.0	186.1
64 3-1F5/15	1.6	160M	140	821	498	365	317	238	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	350	99.0	186.1
64 3-0F5/18.5	1.6	160L	140	821	542	365	317	238	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	350	99.0	196.5
64 4-3F5/18.5	1.6	160L	140	893	542	365	317	238	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	350	108.0	205.5
64 4-2F5/18.5	1.6	160L	140	893	542	365	317	238	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	350	108.0	205.5
64 4-1F5/22	1.6	180	140	893	577	365	360	268	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	350	116.0	279.0
64 4-0F5/22	1.6	180	140	893	577	365	360	268	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	350	116.0	279.0
64 5-3F5/30	1.6	200	140	980	658	365	399	300	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	400	128.0	356.0
64 5-2F5/30	1.6	200	140	980	658	365	399	300	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	400	128.0	356.0
64 5-1F5/30	1.6	200	140	980	658	365	399	300	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	400	128.0	356.0
64 5-0F5/30	1.6	200	140	980	658	365	399	300	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	400	128.0	356.0
64 6-3F5/30	1.6	200	140	1052	658	365	399	300	190	251	266	331	Ø100	Ø140	Ø180	Ø220	20	8	Ø18	Ø14	45	400	136.0	364.0
64 6-2F5/30	2.5	200	140	1052	658	365	399	300	190	251	266	331	Ø100	Ø140	Ø190	Ø235	26	8	Ø22	Ø14	45	400	136.0	364.0
64 6-1F5/37	2.5	200	140	1052	658	365	399	300	190	251	266	331	Ø100	Ø140	Ø190	Ø235	26	8	Ø22	Ø14	45	400	136.0	378.0
64 6-0F5/37	2.5	200	140	1052	658	365	399	300	190	251	266	331	Ø100	Ø140	Ø190	Ø235	26	8	Ø22	Ø14	45	400	136.0	378.0
64 7-3F5/37	2.5	200	140	1124	658	365	399	300	190	251	266	331	Ø100	Ø140	Ø190	Ø235	26	8	Ø22	Ø14	45	400	139.0	381.0
64 7-2F5/37	2.5	200	140	1124	658	365	399	300	190	251	266	331	Ø100	Ø140	Ø190	Ø235	26	8	Ø22	Ø14	45	400	139.0	381.0
64 7-1F5/37	2.5	200	140	1124	658	365	399	300	190	251	266	331	Ø100	Ø140	Ø190	Ø235	26	8	Ø22	Ø14	45	400	139.0	381.0

3) AEG motor dimensions

4) 1,6 MPa=16 bar

2,5 MPa=25 bar

PACKING TABLE
EVM(.) 64

PUMP TYPE EVM(.)	PUMPS						PUMPS WITH MOTOR ~3					
	Packing [mm]			Weight [kgf] EVM(G)	Weight [kgf] EVM(L)	Pack Type	Packing [mm]			Weight [kgf] EVM(G)	Weight [kgf] EVM(L)	Pack Type
	X	Y	Z				X	Y	Z			
64 1-1F5/4.0	400	400	780	69	76	2	400	400	1047	101.1	108.1	2
64 1-0F5/5.5	400	400	780	75	82	2	400	400	1047	126.6	133.6	2
64 2-2F5/7.5	400	400	780	79	87	2	400	400	1047	131.4	138.4	2
64 2-1F5/11	400	400	1047	92	100	2	500	1350	545	185.5	194.5	3
64 2-0F5/11	400	400	1047	92	100	2	500	1350	545	185.5	194.5	3
64 3-3F5/15	400	400	1047	97	106	2	500	1540	540	191.1	200.1	3
64 3-2F5/15	400	400	1047	97	106	2	500	1540	540	191.1	200.1	3
64 3-1F5/15	400	400	1047	97	106	2	500	1540	540	191.1	200.1	3
64 3-0F5/18.5	400	400	1047	97	106	2	500	1540	540	195.5	204.5	3
64 4-3F5/18.5	400	400	1047	105	115	2	500	1540	540	203.5	213.5	3
64 4-2F5/18.5	400	400	1047	105	115	2	500	1540	540	203.5	213.5	3
64 4-1F5/22	400	400	1047	112	123	2	610	1750	593	264.0	275.0	3
64 4-0F5/22	400	400	1047	112	123	2	610	1750	593	264.0	275.0	3
64 5-3F5/30	480	480	1147	126	138	2	610	1750	593	325.0	337.0	3
64 5-2F5/30	480	480	1147	126	138	2	610	1750	593	325.0	337.0	3
64 5-1F5/30	480	480	1147	126	138	2	610	1750	593	325.0	337.0	3
64 5-0F5/30	480	480	1147	126	138	2	610	1750	593	325.0	337.0	3
64 6-3F5/30	480	480	1297	134	146	2	635	2130	587	394.0	406.0	3
64 6-2F5/30	480	480	1297	134	146	2	635	2130	587	394.0	406.0	3
64 6-1F5/37	480	480	1297	134	146	2	635	2130	587	408.0	420.0	3
64 6-0F5/37	480	480	1297	134	146	2	635	2130	587	408.0	420.0	3
64 7-3F5/37	480	480	1297	136	149	2	635	2130	587	410.0	423.0	3
64 7-2F5/37	480	480	1297	136	149	2	635	2130	587	410.0	423.0	3
64 7-1F5/37	480	480	1297	136	149	2	635	2130	587	410.0	423.0	3