

SQDL&SQXL

Model	Single-Phase	Three-Phase	Power		Outlet Inch	Max.Flow m ³ /h	Max.Head m	Dim. mm	G.W. (kg)	20' Loading Qty pcs
			kW	HP						
SQD15-12-0.25L	-	-	0.25	0.33	25	5	14	360×160×200	5	2647
SQD15-17-0.37L	-	-	0.37	0.5	25	6	18	385×160×220	7	2499
SQD15-25-0.55L	-	-	0.55	0.75	25	5	26	395×190×220	9.5	1776
SQD3-18-0.55L	-	-	0.55	0.75	32	8	20	410×180×220	9.5	1715
SQD10-12-0.55L	-	-	0.55	0.75	38	15	18	410×210×220	9.5	1598
SQD15-7-0.55L	-	-	0.55	0.75	51	24	9	410×210×220	9.5	1598
SQD15-32-0.75L	-	-	0.75	1	25	8	33	420×210×230	11.5	1606
SQD3-24-0.75L	-	-	0.75	1	32	9	25	410×190×220	11.5	1715
SQD8-18-0.75L	-	-	0.75	1	38	15	20	420×190×230	11	1614
SQD10-16-0.75L	-	-	0.75	1	51	15	20	420×190×230	11	1614
SQD15-10-0.75L	-	-	0.75	1	64	36	12	420×220×240	11.5	1363
SQD25-6-0.75L	-	-	0.75	1	76	35	11	420×220×260	11.5	1262
SQD30-6-0.75L	-	-	0.75	1	76	45	11	450×280×225	13.5	1103
SQD3-30-1.1L	-	-	1.1	1.5	25	10	31	450×280×225	15	1070
SQD14-16-1.1L	-	-	1.1	1.5	51	29	18	470×280×215	15	1069
SQD15-14-1.1L	-	-	1.1	1.5	64	29	18	470×280×215	15	1069
SQD40-6-1.1L	-	-	1.1	1.5	76	60	10	505×280×215	18	990
-	-	SQX8-18-0.75L	0.75	1	38	15	20	420×195×230	10.5	1262
-	-	SQX10-16-0.75L	0.75	1	51	15	20	420×195×230	10.5	1103
-	-	SQX30-6-0.75L	0.75	1	76	45	11	455×280×215	13	1069
-	-	SQX3-30-1.1L	1.1	1.5	25	10	31	455×280×215	12	1103
-	-	SQX14-16-1.1L	1.1	1.5	51	29	18	470×280×215	15	1069
-	-	SQX15-14-1.1L	1.1	1.5	64	29	18	470×280×215	15	1069
-	-	SQX40-6-1.1L	1.1	1.5	76	60	10	505×280×215	17	990
-	-	SQX25-12-1.5L	1.5	2	64	37	18	505×280×215	17	990
-	-	SQX40-9-1.5L	1.5	2	76	61	12	530×280×215	19	990