

SWQ(D)(≤7.5KW)

Model		Power		Outlet	Max.Flow	Max.Head	The max.	Dim.	Weight (kg)		20' Loading Qty
Single-Phase	Three-Phase	kW	HP	mm	m³/h	m	flow particle mm	mm	G.W.	N.W.	pcs
SWQD6-12-0.55	-	0.55	0.75	1.5"	16	14	20	470×250×250	20.5	19	1150
SWQD6-16-0.75	-	0.75	1	1.5"	22	18	20	470×250×250	22.5	21	1150
SWQD10-10-0.75	-	0.75	1	50	16	16	20	520×210×275	29	26	968
SWQD15-9-1.1	-	1.1	1.5	50	24	14	20	540×240×280	32	29	968
SWQD7-15-1.1	-	1.1	1.5	1.5"	22	18	20	540×240×280	31	28	1150
-	SWQ6-16-0.75	0.75	1	1.5"	22	18	20	470×250×250	21.5	20	968
-	SWQ10-10-0.75	0.75	1	50	16	16	20	520×210×275	29	26	768
-	SWQ15-9-1.1	1.1	1.5	50	24	14	20	540×240×280	32	29	768
-	SWQ7-15-1.1	1.1	1.5	1.5"	22	18	20	540×240×280	31	28	768
-	SWQ18-15-1.5	1.5	2	50	42	20	20	610×260×305	46	41	567
-	SWQ25-7-1.5	1.5	2	65	38	14	25	610×260×305	39	35	567
-	SWQ9-22-2.2	2.2	3	50	32	26	20	635×260×348	47	42	486
-	SWQ15-20-2.2	2.2	3	50	34	24	20	635×260×348	50	44	486
-	SWQ25-15-2.2	2.2	3	65	18	19	20	635×260×348	50	45	486
-	SWQ27-15-2.2	2.2	3	50	50	19	28	635×260×348	50	45	486
-	SWQ42-9-2.2	2.2	3	50	52	19	25	655×270×325	52	47	504
-	SWQ37-13-3	3	4	65	87	18	25	720×320×390	61	61	336
-	SWQ15-30-3	3	4	50	34	34	25	635×260×330	53	48	486
-	SWQ25-20-3	3	4	65	46	25	25	635×260×330	54	49	486
-	SWQ43-13-3	3	4	80	75	21	25	720×320×390	68	61	336
-	SWQ50-10-3	3	4	80	87	19	25	720×320×390	68	61	336
-	SWQ40-15-4	4	5.5	50	92	22	25	755×325×395	81	73	324
-	SWQ60-10-4	4	5.5	100	95	19	43	800×335×395	83	75	324
	SWQ15-40-5.5	5.5	7.5	50	55	44	25	755×325×395	85	78	324
	SWQ30-30-5.5	5.5	7.5	65	42	37	25	800×320×380	88	80	294
	SWQ65-15-5.5	5.5	7.5	100	116	26	30	840×395×475	103	93	175
	SWQ65-20-7.5	7.5	10	100	140	27	30	395×355×1100	128	115	120
	SWQ80-15-7.5	7.5	10	100	140	27	30	395×355×1100	128	115	120
	SWQ100-10-7.5	7.5	10	100	140	28	30	395×355×1100	131	118	120