



ENGINEERING INFORMATION

TYPE 1041A			CAPACITY										
			m ³ /h	180	170	157	144	122	108	94	77	35	14
KW	7.5	OUTLET 4 in	l/s	50	47.3	43.6	40	34	30	26	21.4	10	4
HP 10			HEIGHT										
			m	2	4	6	8	11	13	15	17	21	23
R.P.M	1450	weight 225kg											

TYPE 1041B			CAPACITY										
			m ³ /h	69	60	54	48	42	36	30	23	15	6
KW	7.5	OUTLET 4 in	l/s	19.2	16.7	15	13.3	11.7	10	8.3	6.4	4.2	1.7
HP 10			HEIGHT										
			m	21	22	22.5	23	23.5	24	24.5	25	25.5	26
R.P.M	1450	weight 225kg											

TYPE 1042			CAPACITY										
			m ³ /h	112	109	104	95	90	83	68	60	48	
KW	7.5	OUTLET 4 in	l/s	31.1	30.3	28.9	26.4	25	23	18.9	16.7	13.3	
HP 10			HEIGHT										
			m	14	14.5	15	16	16.5	17	18	18.5	19	
R.P.M	1450	weight 225kg											

IP68 - CLASS F - 380 V - 17A - 50HZ

